

# Wet/Dry Vacuums



## High-performance wet/dry vacuums to fit your cleaning needs.

### Clean longer

Reduce the number of empty/fill cycles with either large capacity 15 gallon/57 liter or 16 gallon/60 liter tank.

### Reduce maintenance costs

Prevent damage to the machine and your facility with a compact, rugged body made of durable polyethylene, backed by a 10-year warranty.

### Multiple options

Choose a unit that's right for the application—whether it's the standard 15 gallon/57 liter unit, a pump out model, which pulls at a high rate and allows for easy emptying into taller sinks, or the battery operated model for greater flexibility and maneuverability. Optional tools and squeegees are available.



V-WD-15  
(shown with optional squeegee)

## Key Benefits

- Prevent vacuum damage with the float shut-off
- Gain easy access to the recovery tank and float shut-off with the flip-top lid
- Choose the wet/dry vacuum that's right for the application; a standard unit, battery operated or a pump-out model



V-WD-16B

# Wet/Dry Vacuums



Features	Specifications*		
Product Name	V-WD-15/V-WD-15S	V-WD-16P	V-WD-16B
<b>Vacuum System</b>			
Airflow at orifice	103 cfm / 2.9 m <sup>3</sup> /hr	112 cfm / 3.17 m <sup>3</sup> /hr	70 cfm / 1.98 m <sup>3</sup> /hr
Water lift at sealed orifice	92 in / 2336 mm	107 in / 2717 mm	70 in / 1778 mm
Motor amps	8.5 A	10.7 A	23 A
Motor diameter	5.7 in / 144 mm	5.7 in / 144 mm	5.7 in / 144 mm
Motor HP	1.3 hp / .97 kW	1.6 hp / 1.2 kW	.75 hp / .56 kW
Motor stages	2 stage	2 stage	3 stage
Motor voltage	120 V	120 V	24 V
Motor power	980 watts	1253 watts	566 watts
<b>Debris Recovery System</b>			
Filter description	Cloth bag / paper bag / intake filter	Cloth bag / paper bag / intake filter	Cloth bag / paper bag / intake filter
Recovery tank wet capacity	15 gal / 57 L	16 gal / 60.57 L	16 gal / 60.57 L
Vacuum hose length	10 ft / 3 m	10 ft / 3 m	10 ft / 3 m
<b>Chassis &amp; Body Construction</b>			
Chassis construction	Rotationally-molded polyethylene	Rotationally-molded polyethylene	Rotationally-molded polyethylene
Caster diameter	4 in / 102 mm	4 in / 102 mm	4 in / 102 mm
Wheel diameter	10 in / 255 mm	10 in / 255 mm	12 in / 305 mm
<b>Power System</b>			
Cord electric (cord length)	50 ft / 15 m	50 ft / 15 m	—
Battery (run time per charge)	—	—	4 hours continuous
<b>Standard Equipment</b>			
Equipment	10 ft x 1.5 in / 3048 mm x 31.8 mm vacuum hose, one cloth and one paper filter bag. Contractor tool kit: dual bend aluminum wand with 14 in / 356 mm squeegee.	10 ft x 1.5 in / 3048 mm x 31.8 mm vacuum hose and cloth filter bag	10 ft x 1.5 in / 3048 mm x 31.8 mm vacuum hose, one cloth and one paper filter bag, two batteries and battery charger
<b>Optional Accessories</b>			
Accessories	Various sized front-mount squeegee kits, wet recovery bag, wet pick-up kit, contractor tool kit and dry tool kit	Various sized front-mount squeegee kits, wet recovery bag, wet pick-up kit, contractor tool kit and dry tool kit	Various sized front-mount squeegee kits, wet recovery bag, cloth filter bag, wet pick-up kit, contractor tool kit and dry tool kit
<b>Standard Equipment</b>			
Equipment (V-WD-15S only)	10 ft x 1.5 in / 3048 mm x 31.8 mm vacuum hose, one cloth and one paper filter bag, and 26 in / 660 mm front mount squeegee	NA	NA
<b>Optional Accessories</b>			
Accessories (V-WD-15S only)	Contractor tool kit: dual bend aluminum wand with 14 in / 356 mm squeegee, wet pick up kit and dry tool kit	NA	NA
<b>Dimensions</b>			
Product Height	37.5 in / 950 mm	35 in / 890 mm	43 in / 1092 mm
Product Length	29 in / 730 mm	30 in / 762 mm	33 in / 840 mm
Product Width	15.5 in / 390 mm	20 in / 510 mm	21 in / 533 mm
Product Weight	44 lb / 20 kg	64 lb / 29.03 kg	97 lb / 44 kg
<b>Approvals</b>	—	CSA, ETL	—
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.		

\*specifications subject to change without notice