# 1610





# **Dual Technology Carpet Cleaner**

- Dry carpets in under 30 minutes with ReadySpace® technology
- Most effective, technologically advanced extractor in the industry
- Power and flexibility in one machine





# Maximum Cleaning Power and Flexibility

Cleaning professionals will appreciate the advantages of 1610's dual technology:

 ReadySpace® Technology
 Carpets cleaned with 1610's ReadySpace® technology are dry and ready for foot traffic in less than 30 minutes.

#### • Restorative Extraction

For periodic restorative cleaning, the 1610 delivers unsurpassed extraction performance.



Tennant's patented ReadySpace® technology creates clean carpet spaces that are dry and ready to use in less than 30 minutes. Consider the benefits of quicker turnaround times:

Reopen rooms and carpeted areas sooner

Keep space accessible to guests and customers

Improve carpet appearance in high traffic areas with more frequent cleanings

Minimize disruption in locations with extended hours

Reduce slip-and-fall risk when transitioning from damp carpet to hard floors

Industry experts have previewed ReadySpace® technology and enthusiastically endorsed it:

"My rather reserved expectations not only were met, they were far exceeded.

ReadySpace® combines effective results with rapid drying. It is the fastest, most efficient maintenance cleaning process to hit the market in years. It's a guarantee for success."

—Jeff Bishop, administrator, clean care seminars, inc. and advisor to trade associations & certification organizations



#### From Clean to Crowd in Minutes

Reopen the space sooner. Faster drying periods and first-rate cleaning performance make it easy to keep carpets clean and ready to use at all times.

#### Open for Business

7·30 AM

Janitorial crews finish cleaning the building's carpeted hallways and lobby using ReadySpace®.

8:00 AM

Carpets are clean, dry and ready to handle the morning's rush of foot traffic.



"Tennant is going in the right direction with ReadySpace®. A facility like ours has an extremely short cleaning window and we need technologies like ReadySpace® that deliver rapid-drying, highly productive cleaning."

—Brian Kingston, facilities manager HARTSFIELD-JACKSON ATLANTA INTERNATIONAL AIRPORT

## **Outstanding Cleaning Performance, Beautiful Results**

Together, frequent ReadySpace® cleanings and periodic restorative extraction tackle the challenges of ongoing carpet maintenance. The results are beautifully clean carpets that last longer.

# Patented ReadySpace® Technology

ReadySpace® technology removes soil before it becomes deeply embedded, leaving carpets cleaner over time and making extraction easier.

- (A) Unique soil-transfer rollers are the basis for ReadySpace®. When damp, these fabric rollers grab dirt from carpet fibers and lift it into the machine.
- (B) Inside, sprayers rinse soil from the rollers, not the carpet.
- (C) Two powerful individual vacuum shoes extract the dirty water into the recovery tank.

Because the carpet itself is never saturated, ReadySpace® technology drastically reduces dry time. In addition, less water usage virtually eliminates wick-back and minimizes odors and molds in the carpet.

# **Restorative Extraction Cleaning**


Tennant pioneered commercial extraction technology. Now with the 1610, Tennant has engineered the most effective deep extractor in the industry. The 1610's unsurpassed performance stems from two important innovations:


#### • Dual Counter-Rotating Brushes

Double agitation and counter-rotation separate more soil from both the front and back of carpet fibers, all in one machine pass.

#### • Superior Vacuum Lift

More power means more dirt and debris is extracted out of the carpet and disposed in the recovery tank.







### **Genuine Tennant Parts**

Get the most from the 1610 with ReadySpace®: Stock genuine Tennant parts and products. Developed in conjunction with the technology, ReadySpace® products are the key to achieving maximum cleaning performance.

#### ReadySpace® Rollers

These unique fabric rollers are the basis for ReadySpace®'s soil-transfer technology.

#### **Extractor Brushes**

Interchangeable with ReadySpace® rollers, these extractor brushes sport a chevron tuft pattern for complete carpet coverage - no gaps like those found with other machines.

#### ReadySpace® Pre-Treatment Chemical

Used in conjunction with ReadySpace®, this companion pre-treatment scores exceptionally well on tests.

#### Pump-Up Sprayer

Pre-spraying is a carpet-care best practice. Use this high-quality two-gallon sprayer to distribute ReadySpace® Pre-Treatment Chemical.



Carpet and Rug Institute (CRI) Seal of Approval – Certified Bronze

# Seeing Is Believing

For a ReadySpace® technology demonstration

1610 DUAL TECHNOLOGY CARPET CLEANER

ReadySpace®

**FEATURES** 

**SPECIFICATIONS** 

**Productivity** 

Recommended Cleaning Speed Maximum per Hour Typical Range per Hour

100 fpm / 30.5 mpm 13,200 ft<sup>2</sup>/hr / 1,226 m<sup>2</sup>/hr 6,000-10,000 ft<sup>2</sup>/hr 560-930 m<sup>2</sup>/hr

50 fpm / 155 mpm 5,500 ft<sup>2</sup>/hr / 510 m<sup>2</sup>/hr 2,000-4,000 ft<sup>2</sup>/hr 185-370 m<sup>2</sup>/hr

1 gpm / 3.8 l/min

**Restorative Extraction** 

**Solution System** 

Solution Tank Capacity

21 gal / 72 L .33 gpm / 1.3 l/min

Nominal Solution Flow Rate Solution Pump - psi

100 psi / 6.9 bar

**Recovery System** 

21 gal / 72 L **Recovery Tank Capacity** Waterlift 120 in / 305 cm Vacuum Motor HP Two .64 HP / .48 KW

Vacuum Motor Stages 3 stage

**Brush System** 

Roller/Brush Length 22 in / 56 cm

Two .625 HP / .315 KW Motor HP

700 Motor RPM

**Drive System** 

Top Transport Speed Up to 250 fpm / 76 mpm .2 HP / .104 KW continuous Transaxle HP

Power & Electrical System

24 V System Voltage **Total Power Consumption** 65 amps Battery Run Time (continuous cleaning rating) 2.5 hours

**Battery Configuration** 4-6 volt 235 AH batteries

**Dimensions/Weights** 

**Product Height** 42 in / 107 cm 60 in / 152 cm **Product Length** Product Width 28 in / 71 cm **Product Weight** 590 lb / 268 kg

340 lb / 154 kg (without batteries)

**Optional Accessories** 

Floor wand, hand tool and hoses

Warranty

10/3/3

The warranty of this unit shall be a minimum of ten (10) years on rotationally molded polyethylene housings and parts to be free from defects and workmanship under normal use and service. The non-polyethylene parts shall have a minimum of a three (3) year warranty under normal use and service. This unit shall also include on-site service labor coverage of warranty items for a minimum of three (3) years.

Tennant

701 North Lilac Drive Minneapolis, MN 55422 USA

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315

www.tennantco.com info@tennantco.com

or additional information, call 800.553.8033.