SAFETY DATA SHEET

1. Identification

Product number	100008136
Product identifier	14 OZ SELECT DUST MOP TREATMENT LB 12PK
Revision date	09-20-2015
Company information	JANITOR'S SUPPLY 5005 SPEEDWAY DRIVE FT WAYNE, IN 46825 United States
Company phone	General Assistance 260-482-8615
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	06
Supersedes date	08-07-2015
Recommended use	Not available.
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1	
Health hazards	Aspiration hazard	Category 1	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			



Signal word	Danger
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
Storage	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	60 - 80
Propane		74-98-6	10 - 20
White Mineral Oil		8042-47-5	10 - 20
Other components below reportable	levels		2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

o. Accidental release mea	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
	Never return spills in original containers for re-use.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or

or detective. Do not spray on a naked fiame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value

	.) •	
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. NIOSH: Pocket Guide t	to Chemical Hazards	
Components	Туре	Value
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
Biological limit values	No biological exposure limits noted	for the ingredient(s).
Appropriate engineering controls	Explosion-proof general and local e	xhaust ventilation.
Individual protection measures	s, such as personal protective equip	ment
Eye/face protection	Face shield is recommended. Wear	safety glasses with side shields (or goggles).
Hand protection	Wear appropriate chemical resistan	t gloves.
Skin protection		
Other	Wear suitable protective clothing.	
Respiratory protection	If permissible levels are exceeded u air-supplied respirator.	ise NIOSH mechanical filter / organic vapor cartridge or an
Thermal hazards	Wear appropriate thermal protective	e clothing, when necessary.
General hygiene considerations		observe good personal hygiene measures, such as washing re eating, drinking, and/or smoking. Routinely wash work o remove contaminants.

9. Physical and chemical properties

Explosive limit - upper (%)

Appearance

Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	-43.7 °F (-42.06 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
	, , , , , , , , , , , , , , , , , , ,
Evaporation rate	Not available.
•	Not available. Not available.
Evaporation rate	Not available.
Evaporation rate Flammability (solid, gas)	Not available. Iosive limits
Evaporation rate Flammability (solid, gas) Upper/lower flammability or exp Flammability limit - lower	Not available. Iosive limits

Not available.

Vapor pressure	35 - 50 psig @20C estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	485.22 °F (251.79 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.748 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.

Conditions to avoidAvoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the
flash point. Contact with incompatible materials.Incompatible materialsStrong oxidizing agents. Fluorine. Chlorine. Nitrates.

Hazardous decomposition No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia.	
Inhalation	Not available.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Symptoms related to the physical, chemical and toxicological characteristics	If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation.	

Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Compor	nents	Species	Test Results		
Distillate	Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)				
	Acute				
	Dermal				
	LD50	Rabbit	> 2000 mg/kg		
			> 2000 mg/kg, 24 Hours		
	Inhalation				
	LC50	Rat	> 7.5 mg/l, 6 Hours		
			> 4.6 mg/l, 4 Hours		
	Oral				
	LD50	Rat	> 5000 mg/kg		
Propane (CAS 74-98-6)					
-	Acute				
	Inhalation				
	LC50	Mouse	1237 mg/l, 120 Minutes		

Components	Species		Test Results
			52 %, 120 Minutes
	Rat		1355 mg/l
			658 mg/l/4h
Vhite Mineral Oil (CAS 8042-47-5	5)		
Acute			
Dermal			
LD50	Rabbit		> 2000 mg/kg, 24 Hours
Inhalation			
LC50	Rat		2.18 mg/l, 4 Hours
Oral			
LD50	Rat		5000.0001 mg/kg
* Estimates for product may b	be based on add	itional component data not shown.	
kin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		on.
Serious eye damage/eye rritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitization	n		
Respiratory sensitization	Not a respirat	ory sensitizer.	
Skin sensitization	This product i	s not expected to cause skin sensitiza	tion.
Germ cell mutagenicity	No data availa mutagenic or		nents present at greater than 0.1% are
Carcinogenicity	This product i	s not considered to be a carcinogen b	y IARC, ACGIH, NTP, or OSHA.
OSHA Specifically Regulate Not listed.	ed Substances	(29 CFR 1910.1001-1050)	
Reproductive toxicity	This product i	s not expected to cause reproductive	or developmental effects.
Specific target organ toxicity - ingle exposure	Not classified.		
Specific target organ toxicity - epeated exposure	Not classified.		
Aspiration hazard	May be fatal i	f swallowed and enters airways.	
Chronic effects	Prolonged or	repeated contact may cause drying, c	racking, or irritation.
12. Ecological information	n		
		s not classified as environmentally has	zardous. However, this does not exclude the
			armful or damaging effect on the environmen
Components		Species	Test Results
Distillates (Petroleum), Hydro	treated Light (C	AS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
White Mineral Oil (CAS 8042- Aquatic	-47-5)		
Fish	LC50	Fish	10000.0001, 96 Hours
* Estimates for product move	hased on add	itional component data not shown.	
Persistence and degradability		ailable on the degradability of this proc	luct
Bioaccumulative potential	No data availa		
Partition coefficient n-octar			
Propane		2.36	
Mobility in soil	No data available.		
Other adverse effects No other adverse environmental effects (e.g. ozono			depletion, photochemical ozone creation
C.1.01 4440136 6116013			ential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.	

14. Transport information

DOT

-	•	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	Special provisions	N82
	Packaging exceptions	306
	Packaging non bulk	None
	Packaging bulk	None
	T I I I I I I I I I I	

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950	
UN proper shipping name	Aerosols, flammable	
Transport hazard class(es)		
Class	2.1	
Subsidiary risk	-	
Label(s)	2.1	
Packing group	Not applicable.	
Environmental hazards	No.	
ERG Code	10L	
Special precautions for use	er Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.	
Other information		
Passenger and cargo aircraft	Allowed.	
Cargo aircraft only	Allowed.	
Packaging Exceptions	LTD QTY	
IMDG		
UN number	UN1950	
UN proper shipping name	AEROSOLS	
Transport hazard class(es)		
Class	2.1	
Subsidiary risk	-	
Label(s)	2.1	
Packing group	Not applicable.	
Environmental hazards		
Marine pollutant	No.	
EmS	F-D, S-U	

Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. LTD QTY Not applicable.



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. **CERCLA Hazardous Substance List (40 CFR 302.4)** Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Propane (CAS 74-98-6)

US. Rhode Island RTK

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Revision date Version #	03-09-2015 09-20-2015 06
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names