

Respect

5005 Speedway Drive Fort Wayne, IN 46825 Phone 260-482-8615 Fax 260-483-5598

EMERGENCY INFOTRAC 800-535-5053

SAFETY DATA SHEET

SECTION 2 – HAZARDS IDENTIFICATION								
EMERGENCY OVERVIE	W		^					
Color:	white, milky	Signal Word: Warning						
Physical State:	liquid	GHS Classification:	Oral Toxicity : Category 5 Serious Eye Damage/Irritation: Category 2B					
Odor:	typical acrylic odor		Skin Corrosion/Irritation: Category 2					
POTENTIAL HEALTH EF	FECTS							
Primary routes of expos	ure: Skin contact and inha	alation.						
Signs and symptoms of	acute exposure: The pro	duct, in the form supplied, is not	anticipated to produce significant adverse human health effects.					
Acute Eye: Slightly irritati	ng. (data for solvent comp	oonent)						

Acute Skin: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

Acute Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation.

Acute Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Remarks: Handle in accordance with good industrial hygiene and safety practice. Dried product may stick to the skin causing irritation upon removal.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS					
INGREDIENT	CAS NUMBER	INGREDIENT % RANGE			
DEG Ethyl Ether	111-90-0	1 - 5%			
Ethanol, 2-butoxy-, phosphate (3:1)	78-51-3	1 - 5%			

SECTION 4 – FIRST AID MEASURES

Eyes: Immediately flush eye(s) with plenty of water.

Skin: In case of contact, Immediately flush skin with plenty of water. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Ingestion: If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

Inhalation: If inhaled, remove victim to fresh air.



Respect

SECTION 5 - FIRE FIGHTING MEASURES

FIRE HAZARD DATA:

Flash Point and Method: Not Determined

Flammability Limits (vol/vol%): LOWER: No data available

UPPER: No data available

Extinguishing Media (suitable): Carbon dioxide (CO2), Dry chemical, Foam, water spray Protective Equipment: Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear)

and self-contained breathing apparatus (pressure demand/NIOSH approved or equivalent).

Further Firefighting Advice: Fire fighting equipment should be thoroughly decontaminated after use.

Fire and Explosion Hazards: When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

SECTION 6 - ACCIDENTAL RELEASE MEASURES

In case of spill or leak: Prevent further leakage or spillage if ou can do so without risk. Ventilate the area. Avoid generation of vapors. Contain and collect spillage with non-combustible absorbent material such as clean sand, earth, diatomaceous eart or non-acidic clay and place into suitable properly labeled containers for prompt disposal. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

SECTION 7 - HANDLING AND STORAGE

Handling: Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

Storage: Keep in a dry, cool place. This material is not hazardous under normal storage conditions; however, material should be stored in closed containers, in a secure area to prevent container damage and subsequent spillage. Store in upright position only. Keep container closed when not in use.

Storage Stability: Stable under normal conditions. May coagulate if frozen at 0°C (32°F). Material may develop bacteria odor on long term storage.

Storage Incompatibility - General:

Store separate from: Strong bases, Strong oxidizing agents, Strong acids May cause coagulation: Multivalent metal salts Temperature tolerance – Do not store below: - 34 °F (1 °C) Temperature tolerance – Do not store above: 100 °F (38 °C)

SECTION 8 – EXPOSURES CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

DEG Ethyl ether: 25 ppm TWA (Source: U.S. OSHA)

Only those components with exposure limits are printed in this section. Engineering, respritory, eye/face and skin protection measure outlined below should be followed to avoid overexposure.

Engineering Controls: Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce

exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Respiratory Protection: Avoid breathing vapor or mist. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components (full facepiece recommended). Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.



Respect

Eye/Face Protection: Use good industrial practice to avoid eye contact.

Skin Protection: Minimize skin contamination by following good industrial hygiene practice. When handling this material, gloves of the following type(s) should be worn: Neoprene, nitrile, Polyvinylchloride, Natural Rubber, butyl-rubber, Chlorinated polyethylene, polyethylene (PE), ethyl vinyl alcohol laminate (EVAL).

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Color:	white, milky	Vapor Density: No data available	
Physical State:	liquid	Vapor Pressure: No data available	
Odor:	Typical Acrylic Odor	Boiling Point: 212 °F (100 °C) (data for Water (7732-18-5))	
pH:	8.5 within 0.5	Freezing Point: 32 °F (0 °C) (data for Water (7732-18-5))	
Density:	8.65 #/gallon	Solubility in water: miscible	
Specific Gravity, g/ml	1.04 Water=1 (liquid)	VOC: 149 g/L (1.25 lb/gal)	

SECTION 10 – STABILITY AND REACTIVITY

Stability: This material is chemically stable under normal and anticipated storage, handling and processing conditions.

Stability-Conditions to avoid: See HANDLING AND STORAGE section of this MSDS for specified conditions. See Hazardous Decomposition Products below.

Materials to Avoid: Strong acids, Strong bases, Strong oxidizing agents

May cause coagulation: Multivalent metal salts

Hazardous Decomposition Products: Thermal decomposition giving flammable and toxic products : Hazardous organic compounds, Carbon oxides Hazardous Polymerization: Hazardous polymerization does not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Data for this material and/or its components are summarized below.

Other information

The information presented is from representative materials with this Chemical Abstract Service (CAS) Registry number. The results vary depending on the size and composition of the test substance. Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates

Diethylene glycol monoethyl ether (111-90-0)

Acute Toxicity - Lethal Doses Rat > 2 GM/M3 1 HOURS LD50 (Oral) Rat 10.5 G/KG LD50 (Skin) Rabbit 9.14 G/KG Reproductive Effects

Carcinogenicity Not listed by IARC, NTP, or OSHA.

Data for Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)

Acute toxicity Oral: Practically nontoxic to slightly toxic. (rat) LD50 = 4,640 - 13,278 mg/kg. Dermal: No more than slightly toxic. (rabbit) LD50 > 5,000 mg/kg. Inhalation: Practically nontoxic. (rat) 4 h LC0 > 6.4 mg/l. (aerosol) Skin Irritation: Slightly irritating. (rabbit) Irritation Index: 2.32. (4 h) Eye Irritation: Slightly irritating. (rabbit)



Respect

Skin Sensitization:

Not a skin sensitizer. Buehler Test. (guinea pig) No skin allergy was observed Skin sensitizer. LLNA: Local Lymph Node Assay. (mouse) Skin allergy was observed. Repeated dose toxicity Subchronic oral administration to rat / affected organ(s): liver, heart / signs: changes in organ weights, changes in organ structure or function, blood chemistry changes, changes in body weight Repeated dermal administration to rabbit / affected organ(s): skin / signs: Irritation / No adverse systemic effects reported. Genotoxicity Assessment in Vitro: No genetic changes were observed in laboratory tests using: bacteria, animal cells Genotoxicity Assessment in Vivo: No genetic changes were observed in a laboratory test using: mice **Developmental toxicity** Exposure during pregnancy. oral (rat) / No birth defects were observed. Human experience Skin contact: Skin: No skin allergy was observed. (studied using human volunteers)

SECTION 12 – ECOLOGICAL INFORMATION

Chemical Fate and Pathway Data on this material and/or its components are summarized below.

 Data for Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)

 Biodegradation:

 Readily biodegradable. (28 d) biodegradation 97 %

 Octanol Water Partition Coefficient: log Pow 3.75

 Ecotoxicology

 Data for Ethanol, 2-butoxy-, phosphate (3:1) (78-51-3)

 Aquatic toxicity data:

 Slightly toxic. Oncorhynchus mykiss (rainbow trout) 96 h LC50 = 24 mg/l

 Slightly toxic. Pimephales promelas (fathead minnow) 96 h LC50 = 11.2 mg/l

 Aquatic invertebrates:

 Slightly toxic. Daphnia magna (Water flea) 48 h EC50 = 53 mg/l

 Algae:

 Slightly toxic. Pseudokirchneriella subcapitata (green algae) 72 h EC50 = 61 mg/l

 Microorganisms:

Practically nontoxic. Activated sludge 3 h EC50 > 1,000 mg/l

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste disposal:

I

Disposal via incineration is recommended. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

SECTION 14 – TRANSPORT INFORMATION

US Department of Transportation (DOT): not regulated (for containers less than 1,000 lbs. net)



Respect

. Toxic Substances Cor	trol Act	TSCA	The componer	ts of this product are all on the TSCA Inventory.
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 144)		DSL		contains one or several components that are not on the L nor NDSL lists.
The components in this properties in this properties in the properties of the proper	Regulations 02 Extremely Hazardous (oduct are either not SARA S 11/312 Hazard Categories: d (chronic) health hazard	ection 302 reg	gulated or regulate	d but present in
SARA Title III – Section 3	13 Toxic Chemicals:			
Chemical Name	Cas-No.		ninimis centration	Reportable Threshold:
Ethanol, 2-butoxy-, Phosphate (3:1)	78-51-3	1.0%)	
DEG Ethyl Ether	111-90-0	1.0%	1	
Comprehensive Environ Quantity (RQ):	mental Response, Compe	nsation, and L	Liability Act (CER	CLA) - Reportable
	<u>(</u>	nsation, and L <u>Cas-No.</u> :06-87-6	Liability Act (CER	CLA) - Reportable Reportable quantity 5000 lbs.
Quantity (RQ):	um salt 5	Cas-No.	Liability Act (CER	
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammonin	um salt 5 DH)) 1	<u>Cas-No.</u> 06-87-6	Liability Act (CER	Reportable quantity 5000 lbs.
Quantity (RQ): Chemical Name Carbonic acid, diammoni Potassium hydroxide (K(Ammonium hydroxide ((N	um salt 5 DH)) 1	<u>Cas-No.</u> 06-87-6 310-58-3 336-21-6	Liability Act (CER	Reportable quantity 5000 lbs. 1000 lbs.
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammoniu Potassium hydroxide (K(Ammonium hydroxide ((N OSHA Regulated carcino	um salt 5 DH)) 1 IHR)(OH)) 1 ogens (NTP, IARC, OSHA I s product present at levels o	Cas-No. 06-87-6 310-58-3 336-21-6 Listed):		Reportable quantity 5000 lbs. 1000 lbs. 1000 lbs.
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammoniu Potassium hydroxide (K((Ammonium hydroxide ((N OSHA Regulated carcino NTP: No component of this anticipated carcinogen by NARC:	um salt 5 DH)) 1 IHR)(OH)) 1 ogens (NTP, IARC, OSHA I s product present at levels g NTP.	Cas-No. 106-87-6 310-58-3 336-21-6 Listed): greater than or	equal to 0.1% is i	Reportable quantity 5000 lbs. 1000 lbs. 1000 lbs. dentified as a known or
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammoniu Potassium hydroxide (K(C Ammonium hydroxide ((N OSHA Regulated carcino NTP: No component of this anticipated carcinogen by IARC: No component of this prod possible or confirmed hum OSHA:	um salt 5 DH)) 1 IHR)(OH)) 1 ogens (NTP, IARC, OSHA I s product present at levels greate NTP. luct present at levels greate an carcinogen by IARC. luct present at levels greate	Cas-No. 106-87-6 310-58-3 336-21-6 Listed): greater than or r than or equal	equal to 0.1% is i	Reportable quantity 5000 lbs. 1000 lbs. 1000 lbs. dentified as a known or
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammoniu Potassium hydroxide (K(C Ammonium hydroxide ((N OSHA Regulated carcino NTP: No component of this anticipated carcinogen by IARC: No component of this prod possible or confirmed hum OSHA: No component of this prod	um salt 5 DH)) 1 IHR)(OH)) 1 ogens (NTP, IARC, OSHA I s product present at levels greate NTP. luct present at levels greate an carcinogen by IARC. luct present at levels greate OSHA.	Cas-No. 106-87-6 310-58-3 336-21-6 Listed): greater than or r than or equal	equal to 0.1% is i	Reportable quantity 5000 lbs. 1000 lbs. 1000 lbs. dentified as a known or
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammoniu Potassium hydroxide (K(C Ammonium hydroxide ((N OSHA Regulated carcino NTP: No component of this anticipated carcinogen by NARC: No component of this prod possible or confirmed hum OSHA: No component of this prod por potential carcinogen by United States – State Reg New Jersey Right to Know	um salt 5 DH)) 1 IHR)(OH)) 1 ogens (NTP, IARC, OSHA I s product present at levels greated NTP. luct present at levels greated an carcinogen by IARC. luct present at levels greated OSHA. gulations	Cas-No. 106-87-6 310-58-3 336-21-6 Listed): greater than or r than or equal	equal to 0.1% is i	Reportable quantity 5000 lbs. 1000 lbs. 1000 lbs. dentified as a known or ed as probable, ed as a carcinogen
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammoniu Potassium hydroxide (K(C Ammonium hydroxide ((N OSHA Regulated carcino NTP: No component of this anticipated carcinogen by VARC: No component of this prod possible or confirmed hum OSHA: No component of this prod possible or confirmed hum OSHA: No component of this prod potential carcinogen by United States – State Reg	um salt 5 DH)) 1 IHR)(OH)) 1 ogens (NTP, IARC, OSHA I s product present at levels of NTP. luct present at levels greate an carcinogen by IARC. luct present at levels greate OSHA. gulations ow	Cas-No. 106-87-6 310-58-3 336-21-6 Listed): greater than or r than or equal	equal to 0.1% is i	Reportable quantity 5000 lbs. 1000 lbs. 1000 lbs. dentified as a known or ed as probable, ed as a carcinogen
Quantity (RQ): <u>Chemical Name</u> Carbonic acid, diammoniu Potassium hydroxide (K(C Ammonium hydroxide ((N OSHA Regulated carcino NTP: No component of this anticipated carcinogen by NARC: No component of this prod possible or confirmed hum OSHA: No component of this prod protential carcinogen by United States – State Reg New Jersey Right to Kno Chemical Name Ethanol, 2-butoxy-, phosp DEG Methyl Ether	um salt 5 DH)) 1 IHR)(OH)) 1 ogens (NTP, IARC, OSHA I s product present at levels of NTP. luct present at levels greate an carcinogen by IARC. luct present at levels greate OSHA. gulations ow	Cas-No. 106-87-6 310-58-3 336-21-6 .isted): greater than or r than or equal r than or equal	equal to 0.1% is identifi I to 0.1% is identifi	Reportable quantity 5000 lbs. 1000 lbs. 1000 lbs. dentified as a known or ed as probable, ed as a carcinogen CAS-No. 78-51-3



SECTION 16 - OTHER INFORMATION

HMIS Rating

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PROTECTIVE EQUIPMENT	в

KEY: 4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal Protection=B (goggles and gloves) HMIS – Hazardous Materials Identification System

PREPARATION INFORMATION

Wayne Concept believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Wayne Concept, Wayne Concept expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.