



# Model R3 Specifications

Cord Electric ReadySpace®

Feature	English / Metric
<b>Brush Drive System</b>	
Roller diameter	4 in / 110 mm
Roller length	15 in / 380 mm
Roller motor power (2 motors)	.3 hp / .22 kW (each)
Roller RPM	450 rpm
Motor RPM	1600 rpm
<b>Chassis/Body Construction</b>	
Chassis construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Wheel descriptions	8 in / 200 mm
<b>Vacuum System</b>	
Airflow at orifice	99 cfm / 2.8 m <sup>3</sup> /min
Vacuum motor amps	7.1 amps / 3.6 amps
Vacuum motor power	1.2 hp / .89 kW
Vacuum motor stages	2 stage
Sealed waterlift	86 in / 2180 mm
<b>Machine Dimensions</b> (Handle folded flat for storage)	
Length	30 in / 750 mm
Machine Width	19 in / 490 mm
Height	28 in / 710 mm
Weight	117 lb / 53 kg
<b>Solution &amp; Recovery System</b>	
Solution tank capacity	5 gal / 19 L
Recovery tank wet capacity	5 gal / 19 L
Spray jet count	1-quick connect
<b>Power Consumption</b>	
Amps	11 amps / 5.5 amps
Voltage	120 V / 230 V
Watts	1320 watts
Cord	50 ft / 15 m
Electrical Safety Approval	ETL Tested for UL & CSA Standards
<b>Pump System</b>	
Solution pump pressure	65 psi / 4.48 bar
Solution pump amps	.5 amp / .25 amp
Solution pump flow rate	.2 gpm / .76 L/min
<b>Sound Level*</b>	
Decibel rating @ operators ear	69 dBA
<b>Warranty</b>	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA