



NSS Enterprises, Inc.

## COLD AND HOT TANK EXTRACTORS

# RALLY 220/220H/500H

Rally carpet extractors provide deep cleaning and versatility. With three models to choose from, there is one for every application and budget. Innovative features, like built in circuit detection, will help your staff make the most of their time.

- Three models:
  - Rally 220 - A 220 PSI cold water carpet extractor.
  - Rally 220H - A 220 PSI heated carpet extractor.
  - Rally 500H - Adjustable pressure from 220 to 500 PSI, heated carpet extractor.
- Heated extraction improves cleaning performance. Hot water helps loosen the bond between the soil and the carpet. The 2000 Watt heaters in the Rally 220H and 500H make your cleaning chemicals more effective, delivering solution at temperatures as high as 190° F.
- Easy maintenance. By removing a single bolt, the tanks on the Rally extractors can be tilted back, revealing the inner workings of the machine.



**DO NO HARM™**

Rally carpet extractors make carpet cleaning efficient and help you extend the life of your carpet. Clean carpet helps limit allergen exposure, keeping building occupants happier and healthier.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

## SPECIFICATIONS

# RALLY 220/220H/500H

<b>Solution Tank</b>	12 Gallons (45 L)
<b>Recovery Tank</b>	12 Gallons (45 L)
<b>Solution Pump</b> 220 and 220H 500H	220 PSI Adjustable, 220 - 500 PSI
<b>Accessory Valve</b>	Quick disconnect, all brass
<b>Vacuum Motor</b> 220 and 220H 500H	Two vacuum motors in parallel 2-stage, 1.25 HP (930 Watts) 3-stage, 1.75 HP (1300 Watts)
<b>Water Lift</b> 220 and 220H 500H	84 inches (213 cm) 120 inches (305 cm)
<b>Hoses</b>	25 ft (7.6 m)
<b>Input Voltage</b>	120V or 240V
<b>Construction</b> Tanks Wheels Casters	Rotomolded polyethylene Two 10-in (25 cm) Two 4-in (10 cm)
<b>Cord</b> 220 220H and 500H	One 25 ft (7.6 m) 12-3 SJTW Two 25 ft (7.6 m) 12-3 SJTW
<b>Sound Level</b>	75 dBA
<b>Dimensions</b> L x W x H	39 x 26 x 17 inches 99 x 66 x 43 cm
<b>Weight</b> 220 220H 500H	86 lbs (39 kg) 106 lbs (48 kg) 127 lbs (58 kg)
<b>Warranty</b>	1 year parts, 1 year labor, 10 years on tanks.
<b>Productivity</b>	500 ft <sup>2</sup> /hr (47 m <sup>2</sup> /hr)



1. Circuit detector helps ensure the heated extractors don't overload the building circuits
2. Built-in priming valve quickly gets the solution pump ready to run.
3. Hose and wand caddy for convenient storage and transport.
4. Durable 12 gallon tanks won't rust or corrode and have a 10 year warranty.
5. Wheel on the handle assists loading the machine into trucks
6. Quick release cord wraps.
7. A 45° elbow on the drain helps divert dirty water into sinks and toilets.



### NSS ENTERPRISES, INC.

3115 Frenchmens Road  
Toledo, OH 43607-2958  
USA

(800) 677-1663 **TEL**  
(419) 531-3761 **FAX**  
info@nss.com

## OPTIONS AND ACCESSORIES



**Hydroglide 2 Wand** - This next-generation carpet wand uses a durable Delrin glide to reduce drag for smooth operation on any surface. Reduce operator fatigue and increase the extraction of soil and moisture from carpet. The rugged polyethylene wand head with tear drop design efficiently collects dirty water. The wand is manufactured with 1.5" aircraft aluminum alloy tubing and only weighs 6.4 pounds.



Two-Jet Stainless Steel Wand



30" Stair Tool.



4" Upholstery Tool

**NSS.COM**