

# V-DMU-14 | DUAL MOTOR UPRIGHT VACUUM



## Delivering reliable performance and increased power at a lower total cost of ownership.

### Reduce maintenance costs and downtime

The V-DMU-14 eliminates four key issues that cause vacuums to fail, thus increasing productivity and lowering service costs versus current commercial vacuums. Backed by a lifetime belt warranty, rest assured that this vacuum will be ready for action.

### Reliable durability

Major components have been proven in commercial applications for over 10 years. This vacuum delivers high value at operating costs up to 58% less than many other commercial vacuums.\*

### Healthy, proven performance

Standard with HEPA 3-stage filtration, the vacuum's cleaning performance is also certified Silver by the Carpet and Rug Institute's (CRI) Seal of Approval program.

Maximizing versatility over single motor uprights, the powerful V-DMU-14 can clean multiple surfaces at the flip of a switch.

\*Based on acquisition cost and assumed consumables (60 bags, 1 brush roll and 8 HEPA filters per year).

## Key Product Features

- LEED qualifying with CRI SOA Silver performance and noise levels less than 70 dBA.
- Increase detailing productivity and cleaning coverage with on-board crevice and upholstery tools and up to 30% longer wand reach than the competition.
- Reduce maintenance costs and downtime with two cord strain reliefs for added cord protection.

# V-DMU-14 | DUAL MOTOR UPRIGHT VACUUM



FEATURES	SPECIFICATIONS*
<b>Product Name</b>	V-DMU-14
<b>Vacuum System</b> Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Vacuum motor watts/amps Water lift at sealed orifice	120 cfm / 3.4 m <sup>3</sup> /m 1.6 hp / 1.19 kW Single stage, thermal protected, clean air 1200 watts / 10 A 65 in/ 1650 mm
<b>Brush Drive System</b> Brush belt description Brush type Brush size Brush motor rating Brush height Brush RPM	PolyV lifetime belt Metal brush roll with natural bristles 12 in / 305 mm length 1.85A / 222W Automatic, self-adjusting 4250 RPM
<b>Filtration</b> Triple filtration system Triple filtration description Vacuum bag capacity	Filter bag, vac motor filter, and HEPA filter High efficiency (99.97%) at 0.3 micron Fill design, 3.8 qt / 3.6 L
<b>Electrical</b> Power cord length	50 ft / 15 m, 3 wire commercial safety-yellow cord with thermal protection switch
<b>Chassis/Body Construction</b> Construction	Injection molded ABS
<b>Accessories</b> Standard	On-board crevice tool, dusting brush with telescopic aluminum wand with 15 ft reach (4:1 stretch)
<b>Dimensions / Weight / Sound Level</b> Length Width Height Weight with cord Sound level (at operator's ear)	12.5 in / 320 mm 14.75 in / 370 mm 44 in / 1120 mm 24 lb / 11 kg < 70 dBA
<b>Approvals</b>	ETL, (US/C)
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.

\*Specifications subject to change without notice

1100-108 V-DMU-14 Cut Sheet 09/11

The Tennant Company logo and other trademarks designated with the symbol "®" are registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors.

**Tennant**  
 701 North Lilac Drive  
 Minneapolis, MN  
 55422 USA

USA/Canada:  
 +1.800.553.8033  
 Quebec:  
 +1.800.361.9050  
 Overseas:  
 +1.763.540.1315

www.tennantco.com  
 info@tennantco.com