DEHUMIDIFIERS





DrizAir® 1200

This compact, highly maneuverable standard dehumidifier removes moisture from everyday spills and reduces humidity in basements, facilities or on construction sites. A proven and durable favorite for almost 20 years!



- Removes up to 18 gallons a day
- Highly mobile compact size
- Hot-gas bypass for fast defrost
- Rugged rotomolded housing stackable!
- · Electronic touch-pad controls
- Rigid handle designed for rugged service
- Semi-pneumatic wheels for easy transport
- Built-in duct attachment ring
- Automatic restart when power is restored after outage
- · Stackable: Stack up to two high for storage



SPECIFICATIONS

- Water removal AHAM (80°F/60%RH): 64 pts. | 30 L/day
- Water removal max. (saturation): 145 pts. | 68.6 L /day
- Process air output: 227 CFM
- Temperature operating range: 33°F-100°F | 1°C-38°C
- Air filter: 4-PRO filter
- Controls: Electronic touchpad
- Dimensions (W × H × D): 20 × 32 × 19.5 × in. | 50 × 83 × 50 cm
- Use weight: 80 lbs. | 36 kg
- Volts: 115V
- Amps: 6.4A
- Frequency: 60Hz
- Air filter: 4-PRO filter
- Drain hose length: 40 ft. | 12 m
- Cord length: 25 ft. | 7.6 m
- Handle: Fixed
- · Housing: Rotomolded polyethylene
- Wheels: Semi-pneumatic
- Safety: ETL listed to CSA 22.2 #92
- Xactimate: WTRDHM

SIZES • OPTIONS

• 104677 (F203-A): One unit