MATERIAL SAFETY DATA SHEET



	1. Product and Company Identification	
Product number	933	
Product name	Gleme Glass Cleaner Wipes	
Effective date	04-Oct-2010	
Company information	Claire Manufacturing Co. 500 Vista Ave. Addison, IL 60101 United States	
Company phone	General Assistance 630-543-7600	
Emergency telephone US	800-424-9300	
Emergency telephone outside US	703-527-3887	
Version #	04	
Supersedes date	31-Mar-2010	
	2. Hazards Identification	
Emergency overview	Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic effects.	
	Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic	
	Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic	
Potential health effects	Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic effects.	
Potential health effects Eyes	Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic effects. Contact with eyes may cause irritation.	
Skin	Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic effects. Contact with eyes may cause irritation. This product may be harmful if it is absorbed through the skin.	

3. Composition / Information on Ingredients		
Components	CAS #	Percent
2-Butoxyethanol	111-76-2	1 - 3
Ethyl Alcohol	64-17-5	1 - 3
Non-hazardous and other components below reportable levels		> 90

4. First Aid Measures

First aid procedures		
Eye contact	Flush eyes with water as a precaution. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops or persists.	
Skin contact	Wash off with soap and water. Get medical attention if irritation develops or persists.	
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or Poison Control Center immediately.	
Ingestion	Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of a large amount does occur, seek medical attention.	
	5. Fire Fighting Measures	
Flammable properties	Runoff to sewer may cause fire or explosion hazard.	

Extinguishing media Suitable extinguishing me	dia Large Fir	es: Water. Water spray,	fog or regular foam	
	· ·			_
Protection of firefighters	Small Fir	es: Dry chemical, CO2,	water spray or regular foan	۱.
Protection of menginers Protective equipment and precautions for firefighters	s including apparatu fire, ISOL for 800 m flame. Fig nozzles. discolora monitor n	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Cool containers with flooding quantities of water until well after fire is out.		
	6. A	ccidental Release	Measures	
Methods for containment	Stop the	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate are Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.		ed material, where this is
Methods for cleaning up		like vermiculite, sand or	uid spill for later disposal. I earth to soak up the produc	Jse a non-combustible ct and place into a container
			pent material (e.g. cloth, fle I flush contaminated area tl	
	Never ret	turn spills in original con	tainers for re-use.	
		7. Handling and St	torage	
Handling			pen flame, heat or other so khaust ventilation. Avoid pr	urces of ignition. Use only in olonged exposure.
Storage	from hea			fluence of heat. Keep away the container dry. Keep in an
	8. Exposı	ure Controls / Pers	onal Protection	
Exposure limits				
ACGIH				
Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
OSHA				
Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Personal protective equipment	t			
Eye / face protection		ally needed.		
Skin protection	Wear ap	propriate chemical resist	ant gloves.	
Respiratory protection		When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.		
	9. Ph	ysical & Chemical	Properties	
Appearance	Sheets.			
	213.8 °F (101.1 °C) estimated			
Boiling point	213.8 °F	(101.1 °C) estimated		
Boiling point Color	213.8 °F White.	(101.1 °C) estimated		

Flash point	>200F		
	22001		
Form	Liquid saturated on wipe.		
Odor	Butyl		
рН	9 - 10		
Physical state	Not available		
Pressure	Not applicable		
Solubility	Partially		
Specific gravity	Unknown		
10	Chemical Stability & Reactivity Information		
Chemical stability	Stable at normal conditions. Risk of ignition.		
Conditions to avoid	Heat, flames and sparks.		
Incompatible materials	None known.		
Hazardous decomposition products	May include oxides of nitrogen.		
	11. Toxicological Information		
Acute effects	Acute LD50: 8992 mg/kg estimated, Rat, Dermal Acute LC50: 89 mg/l/4h estimated, Rat, Inhalation		
Component analysis - LD50			
Toxicology Data - Selected LD50s a	nd LC50s		
2-Butoxyethanol 11	1-76-2 Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat 470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg		
Ethyl Alcohol 64	-17-5 Oral LD50 Rat 7060 mg/kg		
Sensitization	Not expected to be hazardous by OSHA criteria.		
Carcinogenicity			
IARC - Group 1 (Carcinogenic to Hu	mans)		
Ethyl Alcohol 64	-17-5 Monograph 96 [in preparation] (in alcoholic beverages)		
Reproductive effects	Possible reproductive hazard.		
Teratogenicity	Not expected to be hazardous by OSHA criteria.		
	12. Ecological Information		
Ecotoxicity	LC50 45942 mg/L estimated, Fish, 96.00 Hours, EC50 36680 mg/L estimated, Daphnia, 48.00 Hours, IC50 19531 mg/L estimated, Algae, 72.00 Hours, Components of this product have been identified as having potential environmental concerns.		
	13. Disposal Considerations		
Disposal instructions	Consult authorities before disposal. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.		
	14. Transport Information		
Department of Transportation (DOT) Basic shipping requirements: Proper shipping name	Requirements Not Regulated		
	15. Regulatory Information		
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
U.S CERCLA/SARA - Section 313			
	 1-76-2 1.0 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or 		

Occupational Safety and Health		SN (USHA)		
29 CFR 1910.1200 hazardou chemical	s Yes			
CERCLA (Superfund) reportable	quantity			
None				
Superfund Amendments and Re	authorization	Act of 1986 (SARA)		
Section 302 extremely hazardous substance	No	No		
Section 311 hazardous cher	nical Yes			
Hazard categories (311/312)	2) Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No			
Inventory status				
Country(s) or region	Inventory name On inventory (yes/n		On inventory (yes/no)*	
China	Inventory of Existing Chemical Substances in China (IECSC)		Yes	
Europe	European Inventory of New and Existing Chemicals (EINECS)		Yes	
Europe	European List of Notified Chemical Substances (ELINCS)		Yes	
Japan	Inventory of Existing and New Chemical Substances (ENCS)		Yes	
Korea			Yes	
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory Ye			
A "Yes" indicates that all compon	ents of this prod	luct comply with the inventory requirements administered by t	he governing country(s)	
State regulations				
U.S Pennsylvania - RTK (Rigl	nt to Know) List	t		
2-Butoxyethanol Ethyl Alcohol	111-76-2 64-17-5	Present Present		
		16. Other Information		
Further information	HMIS T	rademark Statement		
HMIS® ratings	Health: Flamma Physica			

	Thysical hazard. 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
MSDS sections updated	Product and Company Identification: Product and Company Identification Handling and Storage: Storage Transport Information: Agency Name and Packaging Type/Transport Mode Selection
Prepared by	Regulatory Compliance