



A.P.S.

Acrylic Polymer Seal



Restores worn floors
Protects against abrasion
Intensifies gloss
Extends finish life
Easy to use
Resists black heel marks
Reduces maintenance

Wayne A.P.S. is an acrylic polymer coating designed specifically for use as an undercoat/sealer for all types of resilient flooring, terrazzo and slate. A.P.S. applies easily with a wax applicator or clean wet mop and dries to a smooth streak free luster within 30-40 minutes of application. Once cured, A.P.S. forms a remarkably tough, water clear film that fills and levels worn traffic areas and provides an ideal foundation for subsequent coats of wax or finish. A.P.S. sealed floors generally require fewer coats of finish, display a higher gloss and exhibit greater mark resistance than unsealed floors.

A.P.S. is packed in 4 - 1 gallons per case, and 5 gallon pail.

Product#

J11APS1	1 Gallon
J11APS5	5 Gallon

For use on:

Asphalt
Vinyl
Vinyl Asbestos
Linoleum
Rubber
Slate

Used by:

Hospitals
Offices
Supermarkets
Schools
Retail Stores
Showrooms
Hotels and Motels
Restaurants

Manufactured by:

Wayne Concept Manufacturing Co., Inc.
Fort Wayne, IN 46825 260-482-8615

Serving the maintenance community since 1933

