

Meet the **Endura Family**

Floor Finish for Extended Service Maintenance Programs

Two Products.... One Family

Endura E.S.P. -

- 22% solids
- Brilliant shine
- Extremely durable coating
- 25% more on the floor with each coat
- Packed in 1 gallon J11EESP1 and 5 gallon J11EESP5

Endura 18% -

- 18% solids
- Long lasting shine
- Durable protection
- Fast drying, easy application
- Packed in 1 gallon J11E181 and 5 gallon J11E185



Endura

**A new benchmark of performance
in floor finish**

Extended Service = Big Savings

Time and budget realities are forcing changes in accepted maintenance planning. Many facilities lack the time or staff to strip every floor, every year. By stretching strip cycles from one year to three or four, labor and material savings of 50% or more are possible. Endura minimizes problems inherent in delaying strip-ping. It is made from a new generation of high density polymers that demonstrate greater resistance to dirt penetration, traffic patterns and discoloration than any previously available system. Endura sets a new benchmark of performance and is the ideal foundation for extended service maintenance programs.

Beauty That Lasts

Most finishes look good when applied, Endura sets itself apart in the weeks and months that follow. When other products are scuffed, dull and worn, this one will stand tall. It resists black marks and scuffs, stands up to frequent mopping and scrubbing, and holds its luster with a minimum of care. When repairs are finally necessary, a quick surface scrub and one or two coats applied to wear areas will restore a brilliant, like new appearance.

Hard - Tough - Saves Labor

Resists scuffs, marks and wear, minimal dirt retention. Stands up to repeated cleaning and scrubbing. Takes fewer coats, requiring less maintenance.



Endura 18% & E.S.P.

Floor Finish for Extended Service Maintenance Programs

Directions **Floor Preparation**

Remove all old seal, wax or finish using Red Blitz or The Hammer wax strippers per label directions. Allow floor to dry thoroughly before beginning application.

Initial Application: Conventional Program

Apply 2 or 3 uniform coats using a clean applicator mop and bucket. Allow to dry thoroughly between coats. No buffing is required.

Initial Application: Extended Service Program

Apply 3 coats as above. Wait 24 hours. Apply 3 more uniform coats (Total of 6 coats over 2 days.) Allow to dry thoroughly between coats.

Maintenance

Dust mop traffic areas at least once daily. Do not use oiled mops. Wet mop as needed to remove tracked in dirt, oily soil or ice melt.

Recoating

Dust mop floor to remove loose soil. To remove surface marks and scuffs, scrub with a floor machine or automatic scrubber equipped with a red pad and a solution of 4 oz. Auto Prep per gallon of water. Pick up dirty solution and allow to dry. To maximize appearance, dry buff floor with a red pad prior to re-application. Apply one or two coats using a clean wax applicator mop. Allow to dry thoroughly between coats.

Removal

Wayne Endura is removable with Wayne Red Blitz or The Hammer Heavy Duty Wax Strippers. For specific recommendations consult your Wayne Representative.

Notes:

1. Endura is a non-buff coating and will not respond to conventional dry buffing or burnishing. Small traffic areas may be restored by spray buffing with Wayne Auto Prep or Reply RTU.
2. Abrasive dirt is the greatest cause of accelerated wear. To maximize finish performance, a well designed entrance mat program coupled with regular dust mopping is essential.

Manufactured by:
Wayne Concept Manufacturing Co., Inc.
Fort Wayne, IN 46825 260-482-8615

Serving the maintenance community since 1933



SCAN ME