

# A.P.S.

## Acrylic Polymer Seal



- \* Protects against abrasion and staining
- \* Restores worn older floors
  - \* Intensifies gloss
  - \* Extends finish life
  - \* Easy to use
- \* Safe, Nonflammable and solvent free
- \* Resists black heel marks
- \* Reduces maintenance

Wayne A.P.S. is an acrylic polymer coating designed specifically for use as an undercoat/sealer for all types of resilient flooring, terrazzo and slate. A.P.S. applies easily with a wax applicator or clean wet mop and dries to a smooth streak free luster within 30-40 minutes of application. Once cured, A.P.S. forms a remarkably tough, water clear film that fills and levels worn traffic areas and provides an ideal foundation for subsequent coats of wax or finish. A.P.S. sealed floors generally require fewer coats of finish, display a higher gloss and exhibit greater mark resistance than unsealed floors.

A.P.S. is packed in 4 - 1 gallons per case, and 5 gallon pail.

Product#

J11APS1	1 Gallon
J11APS5	5 Gallon

**For use on:**

Asphalt  
Vinyl  
Vinyl Asbestos  
Linoleum  
Rubber  
Slate

**Used by:**

Hospitals  
Offices  
Supermarkets  
Schools  
Retail Stores  
Showrooms  
Hotels and Motels  
Restaurants

Manufactured by:

**Wayne Concept Manufacturing Co., Inc.**  
Fort Wayne, IN 46825 260-482-8615

*Serving the maintenance community since 1933*

