



Velo Low Profile Airmover

True portability and professional performance. At only 18.6 lbs. (8.4 kg) and stackable up to five high, the Velo delivers rugged reliability, easy maintenance, and high performance. Four operating positions and two speeds for maximum flexibility. Looking for variable amp draw and speed control plus a kickstand? Choose the [Velo Pro](#)!

FEATURES

- Engineered airflow. Patented outlet design ensures even, broad-path airflow for fast, consistent drying across all surfaces.
- Multiple operating positions. Dry floors, ceilings, walls and stairways quickly and efficiently.
- Securely stackable for compact storage – save space on the truck.
- Great portability. Easily carry two units at once – or stack up to six on a hand truck
- Low amp draw with 2-speed versatility.
- Daisy-chain with GFCI outlet. Use up to 6 units per 15 amp circuit for a whopping 5400 CFM of tested – not rated – airflow.
- Durable. Rugged injection-molded housing with easy-carry handle

SIZES • OPTIONS

- **125470 (F504):** One unit



SPECIFICATIONS

- **Air movement:** 885 CFM
- **Amps:** 1.65A (low) - 2.1A (high)
- **Velocity:** 1930 FPM
- **Static pressure:** 1.65 in. (H₂O)
- **Dimensions (D × W × H):**
24 × 18 × 9 in. | 61 × 45.7 × 22.9 cm
- **Weight:** 18.6 lbs. | 8.4 kg
- **Volts:** 115V
- **Frequency:** 60Hz
- **Power:** 185W (motor rating)
- **Control/Speed:** 2-speed rocker switch
- **Cord length:** 15 ft. | 4.6 m
- **Fan:** 6 blade impeller-type
- **Construction:** Injection molded housing; steel wire inlet and outlet grills.
- **Safety:** ETL listed to UL/cUL and CSA standards
- **Sound level (avg.):** 69 dB
- **Xactimate:** WTRDRY